

ICY BOX IB-HUB1419-i3

Front panel for 3.5" bay with USB Type-C®/Type-A hub & card reader



Key features

- 1x USB Type-C® to USB Type-E with a transfer rate of up to 20 Gbit/s
- 1x USB Type-C® with a transfer rate of up to 5 Gbit/s
- 2x USB Type-A with transfer rates of up to 5 Gbit/s
- SD/microSD 3.0 (UHS-I) card readers, up to 104 MB/s
- Supports multi-LUN for memory cards

Packing content

- 1x IB-HUB1419-i3
- 1x USB-A to USB 20 pin cable (50 cm)
- 1x 15 pin SATA to SATA power cable (20 cm)
- 1x Screw set

Technical data

Model	IB-HUB1419-i3
Article no.	61169
EAN code	4250078175032
Colour	Black
Material	Metal
Space required	1x 3.5" bay
Interface to host computer	USB Type-E
Card slots	1x microSD 3.0 (UHS-I) 1x SD 3.0 (UHS-I)

Interface	2x USB Type-A 1x USB Type-C® zu Type-E 1x USB 3.2 Gen 1 Type-C®
Transfer rate	Up to 20 Gbit/s
Power supply	15 pin SATA to SATA power cable
System requirements	One free 3.5" bay space available

ICY BOX **IB-HUB1419-i3**

Front panel for 3.5" bay with USB Type-C®/Type-A hub & card reader



Front panel adapter

A front panel adapter, like IB-HUB1419-i3, offers convenience by placing essential ports and connections directly within reach. You no longer have to search for USB ports at the back of your PC, but have everything you need right at the front. This accessibility not only saves time but also reduces wear on your system's rear ports.



Essential ports at your fingertips

This IB-HUB1419-i3 brings a variety of connection options directly to the front of your PC. It features USB Type-C® ports (20 Gbit/s and 5 Gbit/s), USB Type-A ports (5 Gbit/s), and dual card readers for SD and microSD cards. Simplify your workspace by combining multiple connection types into one easily accessible hub.



Advanced Type-E interface

Equipped with a USB Type-E connector, the IB-HUB 1419-i3 offers direct integration with your motherboard, allowing data transfer speeds of up to 20 Gbit/s. The Type-E connection is designed to meet current and future hardware standards, making it a valuable addition for users who need fast and stable connectivity in their systems.

Logistical data

Packing unit: xx pcs. / carton
Total weight: xx.80 kg
Gross weight (with packing): 0.xx kg
Net weight: 0.xx kg

Dimension/carton: xxx mm
Dimension (with packing): xxx mm
Dimension of article: xxx mm
Country of origin: China